ELSEVIER

Wear 213 (1997) 205

WEAR

Author Index of Volume 213

Andersson, S., 117

Bermejo, J., 1
Blanco, C., 1

Chen, R., 175
Cho, Y.T., 21

Dai, Z.D., 135
Das, S., 41
Dasgupta, R., 41
Diao, D., 21
Dizdar, S., 117

E, J., 123
Elsharkawy, A.A., 47

Gawne, D.T., 123
Gibson, C.T., 72
Girish, B.M., 33
Grigoroudis, K., 103

Hajek, V., 80
Harris, S.J., 200
Hawthorne, H.M., 80
Holgerson, M., 140

Igeland, A., 90
Ilias, H., 90
Ishii, H., 21
Iwabuchi, A., 175

Jha, A.K., 41
Jiang, M., 59

Kamath, R., 33
Knowles, G., 148
Ko, P.L., 148
Komanduri, R., 59

Leu, Z.L., 165
Liu, F., 131
Liu, W., 29
Lu, G., 131

Marsh, H., 1
Martinu, L., 80
Matsunuma, S., 112
Médevielle, A., 13
Menendez, R., 1
Mifune, H., 175

Modi, O.P., 41
Myhra, S., 72

Pan, S.C., 135
Papini, M., 185
Prasad, B.K., 41

Qi, A., 159

Rusnak, K., 80

Sanni, S.A., 98
Satish, B.M., 33
Sharma, S.C., 33
Shimizu, T., 175
Shin, H.S., 175
Spelt, J.K., 185
Stephenson, D.J., 103
Su, Y.L., 165
Sun, J.S., 131
Sun, X.B., 131

Taponat, M.-C., 148
Thévenot, F., 13
Tohgo, K., 21
Tréheux, D., 13

Vlcek, J., 80

Wang, M., 135
Wang, Q.-H., 54
Watson, G.S., 72
Wei, C.S., 165
Weiner, A.M., 200
Wu, C.T., 165

Xue, Q., 29
Xue, Q.-J., 54, 135

Yan, P., 131
Yang, J.Q., 131
Yang, S.R., 135
Yao, S.H., 165
Ye, W., 131
Yegneswaran, A.H., 41
Yinsheng, Z., 159
Yongxin, Q., 159
Yu, S.Y., 21

Zhang, X.S., 135
Zhang, Z., 29

Elsevier Science S.A.

ELSEVIER

Wear 213 (1997) 207–209

WEAR

Subject Index of Volume 213

Abrasion
slurry erosive wear characteristics of a hard faced steel: effect of experimental parameters, 41
modelling low stress abrasive wear, 103
a simple method for monitoring the hardness of thin amorphous carbon-containing coatings, 200
Aluminium matrix composites
temperature dependence of sliding wear behavior in SiC whisker or SiC particulate reinforced 6061 aluminum alloy composite, 21
ATR spectroscopy
the initial step of tribochemical reactions of perfluoropolyether on amorphous carbon, 112

Ball bearings
application of Taguchi method for optimization of finishing conditions in magnetic float polishing (MFP), 59
Ball-on-disk
a simple method for monitoring the hardness of thin amorphous carbon-containing coatings, 200
Blast cleaning
organic coating removal by particle impact, 185
Boundary lubrication
influence of pre-formed boundary layers on wear transition in sliding lubricated contacts, 117
Bubbly oil
study on the viscosity properties of bubbly oil and the static characteristics of journal bearing lubricated with bubbly oil, 159

C/C composites
chemical and physical properties of carbon as related to brake performance, 1
Calibration
lateral force microscopy — a quantitative approach, 72
Carbon fibres
chemical and physical properties of carbon as related to brake performance, 1
Carbon gasification
chemical and physical properties of carbon as related to brake performance, 1
Carbon nitride films
tribological study of CN_x films prepared by reactive d.c. magnetron sputtering, 80
Chemo–mechanical polishing
application of Taguchi method for optimization of finishing conditions in magnetic float polishing (MFP), 59
Coatings
organic coating removal by particle impact, 185
a simple method for monitoring the hardness of thin amorphous carbon-containing coatings, 200
Collisions
organic coating removal by particle impact, 185
Composites
effect of SiC particle reinforcement on the unlubricated sliding wear behaviour of ZA-27 alloy composites, 33
Critical load
temperature dependence of sliding wear behavior in SiC whisker or SiC particulate reinforced 6061 aluminum alloy composite, 21
CrN coating
comparison of tribological behavior of three films—TiN, TiCN and CrN—grown by physical vapor deposition, 165

Delamination
friction characteristics and the wear process of metal pairs in sliding contacts—with applications to modelling wear of power plant components, 148
organic coating removal by particle impact, 185
Dielectrical materials
wear resistance of zirconias. Dielectrical approach, 13
Disc brakes
chemical and physical properties of carbon as related to brake performance, 1

Energy relaxation
wear resistance of zirconias. Dielectrical approach, 13
Energy storage
wear resistance of zirconias. Dielectrical approach, 13
Engagement
apparatus for measurement of engagement characteristics of a wet clutch, 140
2-ethyl hexoic acid (EHA) surface-modified TiO_2 nanoparticle
friction and wear properties of a surface-modified TiO_2 nanoparticle as an additive in liquid paraffin, 29

Filled polyetheretherketone (PEEK) composite
wear mechanisms of polyetheretherketone composites filled with various kinds of SiC, 54
Finishing
application of Taguchi method for optimization of finishing conditions in magnetic float polishing (MFP), 59
Finite difference methods
magnetic head–rigid disk interface hydrodynamically lubricated with a power-law fluid, 47
Fretting wear
improving the fretting wear resistance of titanium alloy by laser beam quenching, 135
Friction
chemical and physical properties of carbon as related to brake performance, 1
wear resistance of zirconias. Dielectrical approach, 13
lateral force microscopy — a quantitative approach, 72
tribological study of CN_x films prepared by reactive d.c. magnetron sputtering, 80
influence of pre-formed boundary layers on wear transition in sliding lubricated contacts, 117

Elsevier Science S.A.

apparatus for measurement of engagement characteristics of a wet clutch, 140
friction characteristics and the wear process of metal pairs in sliding contacts—with applications to modelling wear of power plant components, 148
Friction and wear behaviours
friction and wear properties of a surface-modified TiO_2 nanoparticle as an additive in liquid paraffin, 29
Friction coefficient
temperature dependence of sliding wear behavior in SiC whisker or SiC particulate reinforced 6061 aluminum alloy composite, 21

Hardness
effect of SiC particle reinforcement on the unlubricated sliding wear behaviour of ZA-27 alloy composites, 33
a simple method for monitoring the hardness of thin amorphous carbon-containing coatings, 200
Hydrodynamic lubrication
magnetic head–rigid disk interface hydrodynamically lubricated with a power-law fluid, 47

Impact
organic coating removal by particle impact, 185
Ion implantation
tribological properties of nitrogen ion implanted WC–Co, 131

Journal bearing
study on the viscosity properties of bubbly oil and the static characteristics of journal bearing lubricated with bubbly oil, 159

Laser beam quenching
improving the fretting wear resistance of titanium alloy by laser beam quenching, 135
Lateral force microscopy
lateral force microscopy — a quantitative approach, 72
Load capacity
unsteady squeeze film between rectangular plates, 98

Magnetic float polishing (MFP)
application of Taguchi method for optimization of finishing conditions in magnetic float polishing (MFP), 59
Magnetron sputtering
tribological study of CN_x films prepared by reactive d.c. magnetron sputtering, 80
Metal matrix composites
the sliding wear resistance behavior of NiAl and SiC particles reinforced aluminum alloy matrix composites, 175
Morphology
wear mechanisms of polyetheretherketone composites filled with various kinds of SiC, 54

NiAl particle
the sliding wear resistance behavior of NiAl and SiC particles reinforced aluminum alloy matrix composites, 175
Ni–Cr–Mo steel
surface failure mechanisms of Ni–Cr–Mo steel under lubricated sliding, 123
Non-linear rolling contact mechanics
rail head corrugation growth predictions based on non-linear high frequency vehicle/track interaction, 90
Non-Newtonian fluids
magnetic head–rigid disk interface hydrodynamically lubricated with a power-law fluid, 47

Oil additive
friction and wear properties of a surface-modified TiO_2 nanoparticle as an additive in liquid paraffin, 29

Paint removal
organic coating removal by particle impact, 185
Particle flux
modelling low stress abrasive wear, 103
Particle reinforced MMCs
the sliding wear resistance behavior of NiAl and SiC particles reinforced aluminum alloy matrix composites, 175
Perfluoropolyether
the initial step of tribochemical reactions of perfluoropolyether on amorphous carbon, 112
Polishing
application of Taguchi method for optimization of finishing conditions in magnetic float polishing (MFP), 59
Pre-formed boundary layers
influence of pre-formed boundary layers on wear transition in sliding lubricated contacts, 117
Profile development
rail head corrugation growth predictions based on non-linear high frequency vehicle/track interaction, 90

Quasi-steady
unsteady squeeze film between rectangular plates, 98

Rail head corrugation
rail head corrugation growth predictions based on non-linear high frequency vehicle/track interaction, 90
Rail head wear
rail head corrugation growth predictions based on non-linear high frequency vehicle/track interaction, 90
Reynolds number
unsteady squeeze film between rectangular plates, 98
R.f. bias voltage
tribological study of CN_x films prepared by reactive d.c. magnetron sputtering, 80

Sand content
slurry erosive wear characteristics of a hard faced steel: effect of experimental parameters, 41
Scanned probe microscopy
lateral force microscopy — a quantitative approach, 72
Seizure
influence of pre-formed boundary layers on wear transition in sliding lubricated contacts, 117
SiC particles
effect of SiC particle reinforcement on the unlubricated sliding wear behaviour of ZA-27 alloy composites, 33
the sliding wear resistance behavior of NiAl and SiC particles reinforced aluminum alloy matrix composites, 175
Silicon carbide
wear mechanisms of polyetheretherketone composites filled with various kinds of SiC, 54
Silicon nitride
application of Taguchi method for optimization of finishing conditions in magnetic float polishing (MFP), 59
Sliding lubricated contact
influence of pre-formed boundary layers on wear transition in sliding lubricated contacts, 117
Sliding wear
temperature dependence of sliding wear behavior in SiC whisker or SiC particulate reinforced 6061 aluminum alloy composite, 21
tribological study of CN_x films prepared by reactive d.c. magnetron sputtering, 80
friction characteristics and the wear process of metal pairs in sliding contacts—with applications to modelling wear of power plant components, 148
the sliding wear resistance behavior of NiAl and SiC particles reinforced aluminum alloy matrix composites, 175

Sliding wear behaviour
surface failure mechanisms of Ni–Cr–Mo steel under lubricated sliding, 123
Slurry erosion
slurry erosive wear characteristics of a hard faced steel: effect of experimental parameters, 41
Speed of rotation
slurry erosive wear characteristics of a hard faced steel: effect of experimental parameters, 41
Squeeze film
unsteady squeeze film between rectangular plates, 98
Static characteristic
study on the viscosity properties of bubbly oil and the static characteristics of journal bearing lubricated with bubbly oil, 159
Surface failure mechanisms
surface failure mechanisms of Ni–Cr–Mo steel under lubricated sliding, 123

Taguchi method
application of Taguchi method for optimization of finishing conditions in magnetic float polishing (MFP), 59
Temperature
apparatus for measurement of engagement characteristics of a wet clutch, 140
Temperature dependence
temperature dependence of sliding wear behavior in SiC whisker or SiC particulate reinforced 6061 aluminum alloy composite, 21
Ti-based coating
comparison of tribological behavior of three films—TiN, TiCN and CrN—grown by physical vapor deposition, 165
Titanium alloy
improving the fretting wear resistance of titanium alloy by laser beam quenching, 135
Transfer film
wear mechanisms of polyetheretherketone composites filled with various kinds of SiC, 54
Tribochemical reaction
the initial step of tribochemical reactions of perfluoropolyether on amorphous carbon, 112
Tribological behaviour
wear mechanisms of polyetheretherketone composites filled with various kinds of SiC, 54
comparison of tribological behaviour of three films—TiN, TiCN and CrN—grown by physical vapor deposition, 165
Tribological properties
tribological study of CN_x films prepared by reactive d.c. magnetron sputtering, 80
Tribology
tribological properties of nitrogen ion implanted WC–Co, 131

Unsteady
unsteady squeeze film between rectangular plates, 98

Vehicle/track interaction
rail head corrugation growth predictions based on non-linear high frequency vehicle/track interaction, 90
Velocity
unsteady squeeze film between rectangular plates, 98
Viscosity
study on the viscosity properties of bubbly oil and the static characteristics of journal bearing lubricated with bubbly oil, 159

WC–Co
tribological properties of nitrogen ion implanted WC–Co, 131
Wear
chemical and physical properties of carbon as related to brake performance, 1
wear resistance of zirconias. Dielectrical approach, 13
modelling low stress abrasive wear, 103
Wear morphology
modelling low stress abrasive wear, 103
Wear particle
friction characteristics and the wear process of metal pairs in sliding contacts—with applications to modelling wear of power plant components, 148
Wear rate
effect of SiC particle reinforcement on the unlubricated sliding wear behaviour of ZA-27 ailoy composites, 33
Wear response
slurry erosive wear characteristics of a hard faced steel: effect of experimental parameters, 41
Wear scar
friction characteristics and the wear process of metal pairs in sliding contacts—with applications to modelling wear of power plant components, 148
Wear traces
wear mechanisms of polyetheretherketone composites filled with various kinds of SiC, 54
Wear transition
influence of pre-formed boundary layers on wear transition in sliding lubricated contacts, 117
Wet clutch
apparatus for measurement of engagement characteristics of a wet clutch, 140
Wheel/rail contact
rail head corrugation growth predictions based on non-linear high frequency vehicle/track interaction, 90

XPS analysis
friction and wear properties of a surface-modified TiO_2 nanoparticle as an additive in liquid paraffin, 29

ZA-27 alloy
effect of SiC particle re'nforcement on the unlubricated sliding wear behaviour of ZA-27 alloy composites, 33
Zirconia
wear resistance of zirconias. Dielectrical approach, 13